

WEST

Generate Collection

L7: Entry 7 of 26

File: JPAB

Aug 10, 1999

PUB-NO: JP411220354A

DOCUMENT-IDENTIFIER: JP 11220354 A

TITLE: SURFACE ACOUSTIC WAVE NOTCH FILTER

PUBN-DATE: August 10, 1999

INVENTOR-INFORMATION:

NAME

COUNTRY

SEKI, SHUNICHI

ONISHI, KEIJI

TAGUCHI, YUTAKA

SATOU, HIROTERU

TOMITA, YOSHIHIRO

ASSIGNEE-INFORMATION:

NAME

COUNTRY

MATSUSHITA ELECTRIC IND CO LTD

APPL-NO: JP10272160

APPL-DATE: September 25, 1998

INT-CL (IPC): H03 H 9/64; H03 H 9/145; H03 H 9/25

ABSTRACT:

PROBLEM TO BE SOLVED: To provide an SAW(surface acoustic wave) notch filter which has its large attenuation in a blocking area near the pole of a pass band and also has its stable and satisfactory frequency characteristic.

SOLUTION: This notch filter includes a piezoelectric substrate 1, the input and output electric terminals 2 and 3 provided on the substrate 1, and the 1st to 4th serial arm SAW resonators 11 to 14 and a parallel arm SAW resonator 15 which are connected to the serial and parallel arms respectively placed between the terminals 2 and 3. Each of these resonators 11 to 15 has the reflectors 6 placed at both ends of an IDT(inter-digital transducer) 5. In such a constitution, $RLm+RLg=p(Lm+Lg)$ is satisfied (0.95

COPYRIGHT: (C)1999,JPO

WEST

Generate Collection

L7: Entry 11 of 26

File: JPAB

Mar 8, 1996

PUB-NO: JP408065097A

JP 8-65097

DOCUMENT-IDENTIFIER: JP 08065097 A

TITLE: SURFACE ACOUSTIC WAVE FILTER DEVICE

PUBN-DATE: March 8, 1996

INVENTOR-INFORMATION:

NAME

COUNTRY

ICHIKAWA, SATOSHI

KURODA, YASUSHI

ETSUNO, MASAYOSHI

ASSIGNEE-INFORMATION:

NAME

COUNTRY

TOSHIBA CORP

APPL-NO: JP06195454

APPL-DATE: August 19, 1994

INT-CL (IPC): H03 H 9/64; H03 H 9/145

ABSTRACT:

PURPOSE: To reconcile sufficient band widths and out-of-band attenuation amount by adding a notch filter composed of at least one or more resonators to at least one of the input/output of an interdigital transducer (IDT) serially and in parallel.

CONSTITUTION: IDT11 to 13 having reflectors Gr 7 and Gr 8 on the both sides are arranged in a horizontal line on a substrate. The electric signals inputted from a pad 1 pass a serial/parallel resonator, the signals are transmitted to the IDT 11 and the IDT 13, and the surface acoustic waves excited by these IDT are received in the IDT 12 at the center. The pad 1 is serially connected with a resonator (I) and a resonator (II) and the pad 1 is further connected with a resonator (III) in parallel. In this stage, the resonator (I) is composed of reflectors Gr 9 and Gr 10 and the IDT 14 held by the reflectors, the resonator (II) is composed of reflectors Gr 9a and Gr 10a and the IDT 15 held by the reflectors, and the resonator (III) is composed of reflectors Gr 9b and Gr 10 and the IDT 16 held by the reflectors.

COPYRIGHT: (C)1996, JPO

WEST Search History

DATE: Thursday, April 24, 2003

Set Name Query
side by side

Hit Count Set Name
result set

DB=DWPI; PLUR=YES; OP=ADJ

L12 L11 and (series or serial) and (shunt or parallel)

17 L12

L11 (filter with (notch or reject\$)) and resonator

206 L11

DB=EPAB; PLUR=YES; OP=ADJ

L10 (filter with (notch or reject\$)) and resonator

30 L10

DB=JPAB; PLUR=YES; OP=ADJ

L9 (filter with (notch or reject\$)) and resonator

64 L9

L8 L6 and resonator

93 L8

L7 L6 and (series or serial) and (shunt or parallel)

26 L7

L6 filter and (notch or reject\$)

1534 L6

DB=USPT; PLUR=YES; OP=ADJ

L5 L4 and (resonator with (series or serial) with (shunt or parallel))

29 L5

L4 notch filter

3784 L4

L3 L1 and ((series or serial) with (shunt or parallel) with resonator)

37 L3

L2 L1 and ((series or serial) with (shunt or parallel))

448 L2

L1 bandreject\$ filter or band reject\$ filter or reject\$ filter

2373 L1

END OF SEARCH HISTORY